

塑封超快速整流二极管


反向电压 200 ~ 600 V

正向电流 10 A

Plastic Ultra-Fast Recovery Rectifiers

Reverse Voltage 200 ~ 600 V

Forward Current 10 A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力强 High forward surge capability
- 高信赖性 High reliability
- 引线 and 管体皆符合RoHS标准
Lead and body according with RoHS standard
- 型号后缀“-F”标记无卤素产品
Green compound with suffix "-F" on Marking

机械数据 Mechanical Data

- 封装外形: TO-220AC 塑封 Case: TO-220AC Molded plastic
- 环氧树脂: UL易燃等级: 94V-0
Epoxy: UL 94V-0 rate flame retardant
- 引脚: 镀锡, 无铅 Lead: Pure tin plated, lead free
- 安装位置: 任意 Mounting Position: Any
- 安装扭矩: 推荐值 0.3牛*米 Mounting torque: Recommend 0.3 N*m

最大值和特性 TA = 25°C 除非另有规定。

Maximum Ratings & Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

参数 Parameter	符号 Symbols	DFR 10A20	DFR 10A30	DFR 10A40	DFR 10A60	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	200	300	400	600	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	140	210	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	200	300	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	10.0				A
正向不重复浪涌电流 8.3 ms单一正弦半波 Non-repetitive peak forward surge current 8.3 ms singlehalf sine-wave	I _{FSM}	125				A
最大正向电压 @IF=10.0A Maximum forward voltage	V _F	0.98	1.30		1.80	V
最大反向电流 @V _{DC} TA= 25℃ Maximum reverse current	I _R	30				μA
最大反向恢复时间 IF=0.5A , IR=1.0A ,IRR=0.25A MAX. reverse recovery time	T _{rr}	30	40			ns
典型热阻 Typical thermal resistance (Note 1)	RθJC	2.5				℃/W
工作结温和存储温度 Operating junction and storage temperature rang	T _j , T _{STG}	-55 --- +150				℃

备注 Note:


1) 安装在PCB板上, 从PN结到管体的热阻。

1) Thermal resistance from junction to case, PCB mounted.

特性曲线 Characteristic Curves


正向特性曲线 (典型值)

TYPICAL FORWARD CHARACTERISTIC




正向电流降额曲线

FORWARD CURRENT DERATING CURVE



浪涌特性曲线 (最大值)

MAXIMUM NON REPETITIVE
PEAK FORWARD SURGE CURRENT



反向特性曲线

Typical Reverse Characteristics

